

GENERAL VIEW OF MHRB



GENERAL DESCRIPTION

Optima MHRB mobile hydraulic road blockers are designed especially for entrance points that have a threat of vehicle attack or for the ones that have high-security requirements. The drive unit is electro-hydraulic, but in case of power failure, road blocker can be lowered or lifted manually with the help of a hand pump. Typical raise/lower time is 3-5 seconds, in case of emergency, raise/lower time can be as low as 1.5 seconds if hydraulic accumulator added to the system (optional). The main advantage of Mobile Hydraulic Road Blocker is its ability to be towed up away by any vehicle from site to site easily by the help of 4 pistons and wheels.

STEEL STRUCTURE

The road blocker withstands a minimum of 50 tons of load per axle. Cushioned cylinders power the road blocker up as they pivot on multi-sealed bearings. The steel structure is sandblasted. The standard color is RAL1028 yellow / RAL9005 black.

HYDRAULIC POWER UNIT AND CONTROL ELECTRONICS

Normal operating pressure is around 60-110 bars. Coolers or heaters are can be integrated to the hydraulic power unit as an option. Control electronics utilized in hydraulic road blocker is Optima PLC controller. Two keyboards with emergency stop are standard; one desktop, other being integrated into the hydraulic power unit.

ENVIRONMENTAL CONDITIONS AND POWER REQUIREMENT

Between -15°C and + 65°C, 95% non-condensing humidity; 380V, three phase, 50-60Hz (or 220V/440V/etc., three phase, 50-60 Hz, optional by transformer).

OPTIONAL ACCESSORIES

- ⇒ Hydraulic accumulator.
- ⇒ Transformer to convert the power.
- ⇒ DC motor and pump with dry batteries.
- ⇒ It is possible to operate the system by using solar panel with DC motor.
- ⇒ Coolers or heaters.
- ⇒ Different colors.
- ⇒ SCADA or any control system: It is possible to change and check the position of road blocker with touch screen control panel, mobile devices (ios-android), computer, etc.
- ⇒ Red/green traffic lights.
- ⇒ Pair of safety photocells.
- ⇒ Protective construction(tubular) around drive unit.
- ⇒ Uninterrupted power supply (UPS).

SECURITY SYSTEMS | MHRB MOBILE HYDRAULIC ROAD BLOCKER

MODELS

- ⇒ Raised height : From 400-1000mm.
- ⇒ Road Clearance Width : From 2500 to 5200mm.

MAIN BODY MEASUREMENTS AND FOUNDATION

